RAPID DEPLOYMENT SHELTERS

DRIVE-THRU | COMMAND POST | HOSPITAL |

SKU: K9103-42



LARGE TENT

977 Square Feet



DIMENSIONS:

Space: 977 square feet Length: 42.5 feet

Width: 23 feet Height: 10 feet

Door Size: 76"W x 84"H

Drive-Thru Door Size: 18'W x 7'H

Weight: 588 lbs

Box Size: 48"W x 45"H x 50"D Inflation Time: 7-8 min. with 2 pumps. (14-16 min. with 1)

INCLUDED ASSESSORIES:

Interior Walls (4)

7500 Lumen Lighting System w/ Dimmer (3)

Auto Inflator

Inflator/Deflator Pumps (2)

2400W Power Bank

50' and 25' Extension Cords

Hook & Loop Sleeves (60)

Hook & Loop D-Rings (10)

Custom Sign Package (2 Top, 2 Sides)

Storage Bag

INCLUDED TOOLS:

Tie Down Straps (8)

Metal Stakes (18)

Metal Mallets (2)

Drive-on Anchor Plates (8)

3-Step Ladder

50 Gal Rolling Chest

Pallet Box with Lid

OPTIONAL ACCESSORIES:

HVAC System with Ducts

Power Distribution Box

Generator with Wheel Kit

Water Weight Bags



1-800-345-3036 PROPACUSA.COM



CPAI-84 CSFM COMPLIANT





Multipurpose shelters deployed with unmatched efficiency.





SIGNATURE HIGHLIGHTS:

Flexible roll-up door openings with YKK zippers allow for two opening widths: a generous 76 inches for foot traffic or a spacious 16 foot drive-through option. Doors can be secured in the up or down position utilizing attached D-rings. The double hook and loop strapping system on the door exteriors enables tents to interconnect seamlessly while preventing moisture from compromising door seals. Tent floor is easily removable by hook and loop attachment.

Four Oxford nylon privacy walls, each equipped with an adjustable roll-up centerline door, may be attached as needed by hook and loop to the overhead air frames. These walls and door feature a weighted bottom to ensure privacy or can be completely removed to open up additional interior space.

Ten windows with adjustable configurations provide options for natural light, ventilation, or privacy as needed. Rolling down an outer PVC flap ensures privacy while a removable clear vinyl window allows for natural light or ventilation through a mesh liner.

All vinyl windows are easily removable and secured by hook and loop.

For heating and cooling, an HVAC air plenum is included, designed for ease of use and efficiency. Two vertically mounted HVAC ducts route air through the Oxford nylon material and distribute it along the centerline through 2-inch holes.

For lighting, three included UL-rated 7500 Lumen LED String Lighting Systems features a remote-capable dimmer switch. Using the 6-inch hook and loop sleeves, the lights are easily hung and arranged in any configuration needed.

The package includes an inflator/deflator pump for quick setup and deflation. Inflation to full pressure (2.0 PSI) takes 7-8 minutes on two pumps and is accomplished through Air Banks located on opposite corners. The Air Banks feature two inflate/deflate valves and an overpressure valve to prevent damage if overinflated. An included 2400W Power Bank allows for immediate inflation.

A separate fully automatic, 1200W Auto-Inflator system is included to maintain optimal pressure and provide overpressure protection during multi-day deployments. The system offers three settings for low pressure, high pressure and overpressure, causing the pump to add or remove air during daytime heating or nighttime cooling.

All setup and securing tools are included. With 8 tie-down straps, 18 metal stakes and 8 drive-on anchor plates, the structure can be securely tethered to the ground. Optional Water Weight Bags are available for alternative deployments. Additionally, a 3-step ladder is included to reach the interior roofline.

All tools and ancillary equipment are neatly organized in a lockable 50-gallon rolling chest. For long-term storage, a reusable corrugated sleeve pallet box is included, along with an oversized tent storage bag featuring D-ring straps to ensure 'fold challenged' tents make it back in the bag.

