

# RAPID DEPLOYMENT SHELTERS

| SINGLE PERSON DECONTAMINATION SYSTEM |

SKU: K9000-DC



DECON CUBE

52 Square Feet



## DIMENSIONS:

Space: 52 square feet  
Length: 8 feet  
Width: 6.5 feet  
Height: 7.5 feet  
Weight: 60 lbs  
Box Size: 48"W x 45"H x 40"D  
Inflation Time: 2 min.

## INCLUDED ASSESSORIES:

Plumbing System  
> Hoses, Nozzles, Connectors, Adaptor, Clamps  
Hook & Loop Sleeves (35)  
D-Rings with Hook & Loop (5)  
Containment Berm  
Elevation Grids (4)  
Sump Pumps (2)  
Inflator/Deflator Pump  
600W Power Bank

## INCLUDED TOOLS:

Tie Down Straps (4)  
Metal Stakes (4)  
Metal Mallet  
Pallet Box with Lid  
Storage Bag

## OPTIONAL ACCESSORIES:

Custom Side Wall  
Water Collection Bags  
Water Heater



1-800-345-3036  
[PROPACUSA.COM](http://PROPACUSA.COM)

*Know us before you need us.*



ANSI/ISEA 113-2013 COMPLIANT

CPAI-84/CSFM COMPLIANT



SKU: K9000-DC



DECON CUBE

52 Square Feet

Custom Side Wall Available

Water-Resistant Oxford Fabric



PROPACUSA.COM  
800-345-3036

SINGLE PERSON  
DECONTAMINATION SYSTEM

- PREPLUMBED
  - CONTAINMENT BERM
  - SINGLE PERSON SET UP
  - INFLATES IN MINUTES
  - REMOVABLE CURTAINS
  - LOW AND HIGH TIE-DOWNS
  - CUSTOM SIDE WALLS AVAILABLE
  - 6.5'W x 8'L x 7.5'H
  - WEIGHT: 60 lbs
- ADDITIONAL  
DECON SUPPLIES  
AVAILABLE

## SIGNATURE HIGHLIGHTS:

Engineered for user-friendly operation, swift deployment, and strength, the PVC frame features welded seams and is fully ANSI/ISEA 113-2013 compliant. Set up is easily completed by one person and can be fully inflated within 2 minutes.

The Decon Cube comes fully plumbed and attaches to any standard GHT (Garden Hose Thread) water source. All 3-piece nozzles are polypropylene, resistant to chemical attack, and capable of handling pressures up to 150PSI. Water flow rates from individual nozzles range from 0.3 to 1.2GPM each at full cone spray.

The plumbing system includes four water shutoff valves, one handheld sprayer with adjustable pattern, six side-mounted spray nozzles at staggered heights, plus one overhead spray nozzle, and two 380W, 25 GPM sump pumps with an 18-foot cord. An optional 130-gallon water bladder is available for gray water containment.

All walls, doors, and ceilings are hook and loop mounted, allowing for easy removal, or replacing and are constructed of water-resistant opaque Oxford fabric, providing privacy while welcoming natural light into the space. The two 3-panel entry and exit doors feature hook and loop closures to prevent them from fully opening during windy conditions.

Four slip- and chemical-resistant elevation grids measuring 3' x 2' x 2.75" are included. These grids are designed to keep responders and personnel above gray water, promoting safety and a seamless decontamination process.

The system features an inflator/deflator pump and 600W Power Bank for fast setup and deflation in remote areas. The frame-mounted ID plate and QR code directly link users to instructional videos, providing guidance for unfamiliar or untrained personnel.

All storage and securing tools are included. Four tie-down straps and stakes are included to ensure the system is securely tethered to the ground. An oversized, tent storage bag with D-ring straps to help ensure 'fold challenged' tents make it back in the bag and a reusable corrugated plastic pallet box is also included for long term storage purposes.



1-800-345-3036  
PROPACUSA.COM

Know us before you need us.

