

SKU: K9101-16

# RAPID DEPLOYMENT SHELTERS

COMMAND POST | BRIEFING SPACE | SUPPLY STATION |



## SMALL TENT

190 Square Feet



### DIMENSIONS:

Space: 190 square feet

Length: 16.5 feet

Width: 11.5 feet

Height: 9 feet

Door Size: 76" W x 84" H

Weight: 186 lbs

Box Size: 50" W x 48" H x 45" D

Inflation Time: 5 min.

### KIT COMPONENTS:

- (1) PVC frame with RF welded seams
- (1) Removable PVC floor
- (1) Interior White Oxford Wall
- (1) 7,500 Lumen Lighting System w/ Dimmer
- (30) Hook & Loop Sleeves
- (10) D-Rings with Hook & Loop
- (1) 50' Extension Cord
- (1) Custom Sign Package

### INCLUDED TOOLS:

- (1) Inflator/Deflator Pump
- (1) Auto Inflator
- (8) Tie Down Straps
- (14) Metal Stakes
- (4) Drive-on Anchor Plates
- (2) Sledge Hammers
- (1) 3-Step Ladder
- (1) Plastic Pallet Box with Lid
- (1) Tent Storage Bag
- (1) 50 Gallon Rolling Chest



**1-800-345-3036**  
**PROPACUSA.COM**

Know us before you need us.



CPAI-84 CSFM COMPLIANT

SKU: K9101-16

## YOUR TENT. YOUR BRAND.

Each tent includes a custom sign package with your logo. Two small signs above the entry/exit and two larger side signs ensure visibility for your agency.



## SMALL TENT

190 Square Feet

Multipurpose shelters deployed with unmatched efficiency.



### SIGNATURE HIGHLIGHTS:

Flexible roll-up door openings with YKK zippers allow for two opening widths: a generous 76 inches for foot traffic or a spacious 16 foot wide option. Doors can be secured in the up or down position utilizing attached straps and D-rings. The double hook and loop strapping system on the door exteriors enables tents to interconnect seamlessly while preventing moisture from compromising door seals.

One Oxford nylon privacy wall, equipped with an adjustable roll-up centerline door, may be attached by hook and loop to the overhead air frames. The wall and door feature a weighted bottom to ensure privacy. Tent floor is easily removable by hook and loop attachment.

Four windows with adjustable configurations provide options for natural light, ventilation, or privacy as needed. Rolling down an outer PVC flap ensures privacy while a removable clear vinyl window allows for natural light or ventilation through a mesh liner. All vinyl windows are easily removable and secured by hook and loop.

For heating and cooling, an HVAC air plenum is included, designed for ease of use and efficiency. Two vertically mounted HVAC ducts route air through the Oxford nylon material and distribute it along the centerline through 2-inch holes.

A UL-rated 7,500 Lumen LED String Lighting System with dimmer is included for added lighting. Using the 6-inch hook and loop sleeves, the lights are easily hung and arranged in any configuration needed.

The package includes an inflator/deflator pump for quick setup and deflation. Inflation to full pressure (2.0 PSI) takes 5 minutes and is accomplished through two Air Banks located on opposite corners. The Air Banks feature two inflate/deflate valves and an overpressure valve to prevent damage if overinflated.

A separate fully automatic, 1200W Auto-Inflator system is included to maintain optimal pressure and provide overpressure protection during multi-day deployments. The system offers three settings for low pressure, high pressure and overpressure, causing the pump to add or remove air during daytime heating or nighttime cooling.

All setup and securing tools are included. With 8 tie-down straps, 14 metal stakes, and 4 drive-on anchor plates, the structure can be securely tethered to the ground. Optional water weight bags are available for alternative deployments. Additionally, a 3-step ladder is included to reach the interior roofline.

All tools and ancillary equipment are neatly organized in a lockable 50-gallon rolling chest. For long-term storage, a reusable corrugated pallet box is included, along with an oversized tent storage bag featuring D-ring straps to ensure 'fold challenged' tents make it back in the bag.



1-800-345-3036  
PROPACUSA.COM

Know us before you need us.