

# RAPID DEPLOYMENT SHELTERS

| DRIVE-THRU | POINT OF DISTRIBUTION |

SKU: K9104-2L



DRIVE-THRU TENT

1,320 Square Feet



## DIMENSIONS:

Space: 1,320 square feet  
Length: 40 feet  
Width: 33 feet  
Height: 15.5 feet  
Drive-Thru Door Size: 28.5'W x 8'H  
Side Door Size: 76"W x 84"H  
Weight: 1,300 lbs  
Inflation Time: 40-60 min.

## INCLUDED ASSESSORIES:

7,500 Lumen Lighting System w/ Dimmer (4)  
Auto Inflator  
Inflator/Deflator Pumps (8)  
2400W Power Banks (2)  
50' Extension Cords (2)  
Hook & Loop Sleeves (50)  
Hook & Loop D-Rings (10)  
Anchor Plates (4)  
Custom Entry/Exit Signs (4)

## INCLUDED TOOLS:

Tie Down Straps (8)  
Metal Stakes (24)  
Metal Mallets (2)  
3 Step Ladders (2)  
50 Gal Rolling Chests (2)  
Four-Wheel Motorized Hand Truck

## OPTIONAL ACCESSORIES:

Water Weight Bags  
50' Extension Cords



1-800-345-3036  
[PROPACUSA.COM](http://PROPACUSA.COM)

*Know us before you need us.*



CPAI-84 CSFM COMPLIANT

## YOUR TENT. YOUR BRAND.

Each tent includes a custom sign package with your logo. Four large signs above the entry/exits ensure visibility for your agency.



SKU: K9104-2L



## DRIVE-THRU TENT

1,320 Square Feet

Multipurpose shelters deployed with unmatched efficiency.



### SIGNATURE HIGHLIGHTS:

The tent is crafted from PVC material meeting CPAI-84 CSFM standards. With a design that promotes continuous airflow throughout the entire structure, including both walls and ceiling, the ribbed pattern serves a dual purpose by enhancing aesthetics and reinforcing seams for durability. Supporting the tent's robust frame, 10 heavy-duty ground straps contribute to maintaining its shape, ensuring a well-defined structure.

Versatile roll-up door openings with YKK zippers offer multiple configurations: the side doors are a generous 76 inches wide for foot traffic, while the main entry and exits can be fully opened to an expansive 28.5 feet wide at their largest. The roll-up door panels, featuring four on each entry or exit, connect with zippers and can be easily unzipped, rolled up and secured with attached D-rings, allowing for an entry as small as 86 inches wide by 96 inches high. The double hook and loop strapping system on the side door exteriors enables tents to interconnect seamlessly while preventing moisture from compromising door seals.

For lighting, an included UL-rated 30,000 Lumen LED String Lighting System features 2 remote-capable dimmer switches. Using the 6-inch hook and loop sleeves, the lights are easily hung and arranged along the interior as needed.

The package includes 8 inflator/deflator pumps for faster setup and deflation. Inflation to full pressure (2.0 PSI) takes 40-60 minutes and is accomplished through four Air Banks located on each corner. The Air Banks feature two inflate/deflate valves and an overpressure valve to prevent damage if overinflated. Included are two portable 2400W Power Banks to allow for immediate inflation.

A separate fully automatic, 1200W Auto-Inflator system is included to maintain optimal pressure and provide overpressure protection during multi-day deployments. The system offers three settings for low pressure, high pressure and overpressure, causing the pump to add or remove air during daytime heating or nighttime cooling.

For added versatility, the tent is equipped with a total of 16 D-rings along both the exterior and interior of the bottom, as well as 8 top D-rings. These D-rings provide multiple points for securing and anchoring the tent, offering flexibility in setup and ensuring stability in various conditions.

All setup and securing tools for easy assembly by multiple personnel are thoughtfully included. With 8 tie-down straps, 24 metal stakes, two mallets and two 3-step ladders the structure can be securely tethered to the ground. Vehicle Anchors are also included for asphalt/concrete deployments. Plus, all tools and ancillary equipment are neatly organized in two lockable 50-gallon rolling chests.



1-800-345-3036  
[PROPACUSA.COM](http://PROPACUSA.COM)

Know us before you need us.

